NSN 5945-00-969-6547

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-969-6547

Overall Length: 1.375 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.062 inches single mounting facility Overall Height: 1.080 inches Overall Width: 0.400 inches Mounting Slot Width: 0.125 inches single mounting facility

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Contact Surface Treatment:

Gold

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

10.0 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.594 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

5.0 milliamperes dc single winding

NSN 5945-00-969-6547

Electromagnetic Relay - Page 2 of 2



Time Delay: 0.005 seconds fixed operate and release time **Operating Voltage Rating And Type At Specificationified Temp:** 110.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Precious Material And Location:** Contacts silver and contact surfaces gold **Precious Material:** Silver and gold **Terminal Type And Quantity:** 8 pin all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300