

View Online at <https://aerobasegroup.com/nsn/5945-00-971-6592>

Terminal Quantity:

6

Terminal Type:

Threaded stud

Case Material:

Plastic

Environmental Protection:

Dustproof

End Application:

2gvortac, rta-2 antenna, fa-6237 control panel

Mounting Configuration:

Four no. 4-40 thd mtg studs spaced 2-1/4 in. C to c

Voltage Rating:

48.0 volts

Main Contact Form Arrangement:

2a1b

Main Contact Current Type:

Dc

Main Contact Current Rating:

1.0 milliamperes

Meter Movement Current Type:

Dc

Meter Movement Voltage In Volts:

48.000

Meter Movement Current Range:

+330.0/+1000.0 microamperes

Meter Mounting Type:

Flush

Contact Closing Condition:

Decrease value

Reset Facility Feature:

Provided

Lock In Device Type:

Permanent magnet

Release Method:

Electromagnetic

Meter Depth Behind Mounting Flange:

2.484 inches

Mounting Flange Diameter:

3.020 inches

Err Default:

Err default

Special Features:

2 coils, 48 vdc contacts rated at 15 ma

Functional Description:

Meter, relay, (tacan speed-control meter)

Reference Data And Literature:

Mk 13056, instruction book, rtn equipment antenna group, model rta-2, sec 1-12, fa-6237 control panel, pg 10-56; m 13056, fa-6237a control panel, pg 10-13

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T142-k