

View Online at <https://aerobasegroup.com/nsn/5945-00-971-6592>

**Terminal Quantity:**

6

**Terminal Type:**

Threaded stud

**Case Material:**

Plastic

**Environmental Protection:**

Dustproof

**End Application:**

2gvortac, rta-2 antenna, fa-6237 control panel

**Mounting Configuration:**

Four no. 4-40 thd mtg studs spaced 2-1/4 in. C to c

**Voltage Rating:**

48.0 volts

**Main Contact Form Arrangement:**

2a1b

**Main Contact Current Type:**

Dc

**Main Contact Current Rating:**

1.0 milliamperes

**Meter Movement Current Type:**

Dc

**Meter Movement Voltage In Volts:**

48.000

**Meter Movement Current Range:**

+330.0/+1000.0 microamperes

**Meter Mounting Type:**

Flush

**Contact Closing Condition:**

Decrease value

**Reset Facility Feature:**

Provided

**Lock In Device Type:**

Permanent magnet

**Release Method:**

Electromagnetic

**Meter Depth Behind Mounting Flange:**

2.484 inches

**Mounting Flange Diameter:**

3.020 inches

**Err Default:**

Err default

**Special Features:**

2 coils, 48 vdc contacts rated at 15 ma

**Functional Description:**

Meter, relay, (tacan speed-control meter)

**Reference Data And Literature:**

Mk 13056, instruction book, rtn equipment antenna group, model rta-2, sec 1-12, fa-6237 control panel, pg 10-56; m 13056, fa-6237a control panel, pg 10-13

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T142-k