

View Online at <https://aerobasegroup.com/nsn/5945-00-971-8285>

Terminal Quantity:

6

Terminal Type:

Flexible lead and tube plug

Overall Length:

2.000 inches

Length:

6.000 inches

Overall Diameter:

0.750 inches

Case Material:

Metal

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Coil Type:

Isolated

Contact Arrangement:

Single pole, double throw

Input Voltage Rating:

9.6 ac pounds per hour wet

Output Voltage Rating:

10.0 ac volts

Unit Type:

Electromechanical

Output Frequency Rating:

Between 1.0 hertz and 850.0 hertz

Output Current Rating:

1.0 milliamperes

Base Type:

Standard base

Hermetically Sealed Feature:

Provided

Input Current Rating:

38.0 milliamperes

Drive Voltage Relationship To Input Voltage:

Unequal

Drive Voltage Rating:

9.6 ac pounds per hour wet

Drive Current Relationship To Input Current:

Unequal

Err Default:

Err default

Drive Frequency Rating:

400.0 hertz

Output/Input Voltage Relationship:

Unequal

Reed Type:

Single

Contact Operation Sequence:

Breaks before makes

Contact Voltage Rating:

10.0 dc pounds per hour with retaining chain

Contact Current Rating:

1.0 milliamperes

Phase Angle In Deg:

56.0

Dwell Time Rating In Deg:

170.0

Err Default:

Err default

Err Default:

Err default

Plug In Mounting Feature:

Provided

Base Mounting Size Designation:

4 pin tube

Terminal Pattern Arrangement:

4 pin terminal pattern

Connection Location:

Top

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-k