

View Online at <https://aerobasegroup.com/nsn/5945-00-974-2504>

Thread Class:

2a power takeoff facility stud

Body Style:

Cylindrical frame

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.326 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.326 inches

Body Diameter:

1.490 mils and 1.510 centimeters

Body Length:

1.400 inches

Unthreaded Mounting Hole Diameter:

Between 0.200 inches and 0.210 inches

Maximum Operating Temp:

250.0 degrees fahrenheit

Mounting Base Width:

Between 1.690 inches and 1.710 inches

Inclosure Type:

Fully enclosed

Magnetic Coil Quantity:

1

Electrical Resistance:

Between 22.50 ohms and 26.50 ohms

Duty Type:

Continuous

Terminal Location:

End opposite actuator

Voltage Rating In Volts:

30.0 dc

Mounting Facility Type And Quantity:

4 unthreaded hole

Thready Qty Per Inch (tpi):

24 power takeoff facility stud

Actuator Stroke Type:

Push

Linear Force Delivered:

12.00 pounds

Power Takeoff Connection Type:

External threads

Energizing Stroke Maximum Length:

0.055 inches

Thread Size:

0.375 inches power takeoff facility stud

Mounting Facility Pattern:

Four position rectangular

Thread Series Designator:

Unf power takeoff facility stud

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A134a0