## NSN 5945-00-974-7886

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-00-974-7886             |
|---|
| Overall Length:   |
| 1.320 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.062 inches single mounting facility                                     |
| Overall Height:   |
| 1.090 inches  |
| Overall Width:  |
| 0.440 inches  |
| Environmental Protection:   |
| Hermetic  |
| Unthreaded Mounting Hole Diameter:  |
| 0.096 inches single mounting facility                                     |
| Winding Quantity:   |
| 1   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:   |
| 800.0 ohms single winding   |
| Duty Type:  |
| Continuous  |
| Arc Quenching Method:   |
| Inert gas   |
| Mounting Facility Type And Quantity:                                      |
| 2 unthreaded hole single mounting facility                                |
| Features Provided:  |
| Polarized   |
| Mounting Facility Pattern:  |
| In-line single mounting facility  |
| Nonpile-up Main Contact Arrangement:                                      |
| 2 pole, double throw, one position momentary                              |
| Time Delay:   |
| 0.005 seconds fixed operate and release time                              |
| Operating Voltage Rating And Type At Specificationified Temp:             |
| 26.0 volts dc 25 degrees celsius single winding                           |
| Main Contact Load Current Rating At Maximum Rated Voltage:                |
| 2.0 amperes dc resistive load   |
| Main Contact Maximum Voltage Rating In Volts:                             |
| 32.0 dc   |
| Terminal Type And Quantity:   |
| 8 pin all functions   |

Shelf Life: N/a

## NSN 5945-00-974-7886

Electromagnetic Relay - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

A03300