## NSN 5945-00-977-5760

Electrical Solenoid - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-977-5760

Body Style:   Base end actuator   Case Material:   Any acceptable   Case Surface Treatment:   Any acceptable   Environmental Protection:   Any acceptable   Inclosure Type:   Fully enclosed   Magnetic Coil Quantity:   1   Terminal Location:   Circumference   Voltage Rating In Volts:   28.0 dc   Mounting Facility Type And Quantity:   2 threaded stud   Actuator Stroke Type:   Rotary   Power Takeoff Connection Type:   Slotted-drilled   Mounting Facility Pattern:   Two position in-line   Terminal Type And Quantity:   2 wire lead   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:	
Case Material: Any acceptable Case Surface Treatment: Any acceptable Environmental Protection: Any acceptable Inclosure Type: Fully enclosed Magnetic Coil Quantity: 1 Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Actuator Stroke Type: Rotary Power Takeoff Connection Type: Slotted-drilled Mounting Facility Pattern: Two position in-line Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:	
Any acceptable Case Surface Treatment: Any acceptable Environmental Protection: Any acceptable Inclosure Type: Fully enclosed Magnetic Coil Quantity: I Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Actuator Stroke Type: Rotary Power Takeoff Connection Type: Slotted-drilled Mounting Facility Pattern: Two position in-line Terminal Type And Quantity: 2 wire lead Sheff Life: N/a Unit Of Measure: Demilitarization:	
Case Surface Treatment:Any acceptableEnvironmental Protection:Any acceptableInclosure Type:Fully enclosedMagnetic Coil Quantity:1Terminal Location:CircumferenceVoltage Rating In Volts:28.0 dcMounting Facility Type And Quantity:2 threaded studActuator Stroke Type:RotaryPower Takeoff Connection Type:Slotted-drilledMounting Facility Pattern:Two position in-lineTerminal Type And Quantity:2 wire leadSheff Life:N/aUnit Of Measure:-Demilitarization:	
Any acceptable   Environmental Protection:   Any acceptable   Inclosure Type:   Fully enclosed   Magnetic Coil Quantity:   1   Terminal Location:   Circumference   Voltage Rating In Volts:   28.0 dc   Mounting Facility Type And Quantity:   2 threaded stud   Actuator Stroke Type:   Slotted-drilled   Mounting Facility Pattern:   Two position in-line   Terminal Type And Quantity:   2 wire lead   Shelf Life:   N/a   Inti Of Measure:     Demilitarization:	
Environmental Protection:   Any acceptable   Inclosure Type:   Fully enclosed   Magnetic Coil Quantity:   1   Terminal Location:   Circumference   Voltage Rating In Volts:   28.0 dc   Mounting Facility Type And Quantity:   2 threaded stud   Actuator Stroke Type:   Rotary   Power Takeoff Connection Type:   Slotted-drilled   Mounting Facility Pattern:   Two position in-line   Terminal Type And Quantity:   2 wire lead   Shelf Life:   N/a   Unit Of Measure:   -   Demilitarization:	
Any acceptable Inclosure Type: Fully enclosed Magnetic Coil Quantity: 1 Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Actuator Stroke Type: Rotary Power Takeoff Connection Type: Slotted-drilled Mounting Facility Pattern: Two position in-line Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization:	
Inclosure Type: Fully enclosed Magnetic Coil Quantity: 1 Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Actuator Stroke Type: Rotary Power Takeoff Connection Type: Slotted-drilled Mounting Facility Pattern: Two position in-line Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: 	
Fully enclosedMagnetic Coil Quantity:1Terminal Location:CircumferenceVoltage Rating In Volts:28.0 dcMounting Facility Type And Quantity:2 threaded studActuator Stroke Type:RotaryPower Takeoff Connection Type:Slotted-drilledMounting Facility Pattern:Two position in-lineTerminal Type And Quantity:2 wire leadShelf Life:N/aUnit Of Measure:Demilitarization:	
Magnetic Coil Quantity:1Terminal Location:CircumferenceVoltage Rating In Volts:28.0 dcMounting Facility Type And Quantity:2 threaded studActuator Stroke Type:RotaryPower Takeoff Connection Type:Slotted-drilledMounting Facility Pattern:Two position in-lineTerminal Type And Quantity:2 wire leadShelf Life:N/aUnit Of Measure:Demilitarization:	
1         Terminal Location:         Circumference         Voltage Rating In Volts:         28.0 dc         Mounting Facility Type And Quantity:         2 threaded stud         Actuator Stroke Type:         Rotary         Power Takeoff Connection Type:         Slotted-drilled         Mounting Facility Pattern:         Two position in-line         Terminal Type And Quantity:         2 wire lead         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:	
Terminal Location:CircumferenceVoltage Rating In Volts:28.0 dcMounting Facility Type And Quantity:2 threaded studActuator Stroke Type:RotaryPower Takeoff Connection Type:Slotted-drilledMounting Facility Pattern:Two position in-lineTerminal Type And Quantity:2 wire leadShelf Life:N/aUnit Of Measure:Demilitarization:	
Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Actuator Stroke Type: Rotary Power Takeoff Connection Type: Slotted-drilled Mounting Facility Pattern: Two position in-line Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: 	
Voltage Rating In Volts:28.0 dcMounting Facility Type And Quantity:2 threaded studActuator Stroke Type:RotaryPower Takeoff Connection Type:Slotted-drilledMounting Facility Pattern:Two position in-lineTerminal Type And Quantity:2 wire leadShelf Life:N/aUnit Of Measure:Demilitarization:	
28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Actuator Stroke Type: Rotary Power Takeoff Connection Type: Slotted-drilled Mounting Facility Pattern: Two position in-line Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: 	
Mounting Facility Type And Quantity:2 threaded studActuator Stroke Type:RotaryPower Takeoff Connection Type:Slotted-drilledMounting Facility Pattern:Two position in-lineTerminal Type And Quantity:2 wire leadShelf Life:N/aUnit Of Measure:Demilitarization:	
2 threaded stud Actuator Stroke Type: Rotary Power Takeoff Connection Type: Slotted-drilled Mounting Facility Pattern: Two position in-line Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: 	
Actuator Stroke Type:RotaryPower Takeoff Connection Type:Slotted-drilledMounting Facility Pattern:Two position in-lineTerminal Type And Quantity:2 wire leadShelf Life:N/aUnit Of Measure:Demilitarization:	
Rotary   Power Takeoff Connection Type:   Slotted-drilled   Slotted-drilled   Mounting Facility Pattern:   Two position in-line   Terminal Type And Quantity:   2 wire lead   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:	
Power Takeoff Connection Type:Slotted-drilledMounting Facility Pattern:Two position in-lineTerminal Type And Quantity:2 wire leadShelf Life:N/aUnit Of Measure:Demilitarization:	
Slotted-drilled Mounting Facility Pattern: Two position in-line Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:	
Mounting Facility Pattern: Two position in-line Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:	
Two position in-line Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization:	
Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:	
2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:	
Shelf Life: N/a Unit Of Measure:  Demilitarization:	
N/a Unit Of Measure:  Demilitarization:	
Unit Of Measure:  Demilitarization:	
 Demilitarization:	
No	
Fiig:	
A134a0	