

View Online at <https://aerobasegroup.com/nsn/5945-00-985-7719>

**Terminal Quantity:**

7

**Terminal Type:**

Tube plug

**Mounting Provision:**

Studs

**Overall Length:**

2.250 inches

**Overall Diameter:**

0.750 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**End Application:**

6625-00-753-2114 voltmeter

**Mounting Facility Quantity:**

1

**Mounting Configuration:**

0.125 in. Diameter 40 thd per in. 0.625 in. Lg thd stud

**Coil Type:**

Isolated

**Contact Arrangement:**

Single pole, double throw

**Input Voltage Rating:**

10.0 dc pounds per hour wet

**Output Voltage Rating:**

10.0 ac volts

**Unit Type:**

Electromechanical

**Output Frequency Rating:**

Between 1.0 hertz and 180.0 hertz

**Output Current Rating:**

1.0 milliamperes

**Mounting Facility Size:**

0.112 in. Diameter by 0.625 in. Lg

**Mounting Method:**

Threaded stud mtd

**Hermetically Sealed Feature:**

Provided

**Input Current Rating:**

1.0 milliamperes

**Drive Voltage Relationship To Input Voltage:**

Unequal

**Drive Voltage Rating:**

6.3 ac pounds per hour wet

**Drive Current Relationship To Input Current:**

Unequal

**Err Default:**

Err default

**Drive Frequency Rating:**

Between 1.0 hertz and 180.0 hertz

**Output/input Voltage Relationship:**

Unequal

**Reed Type:**

Single

**Contact Operation Sequence:**

Breaks before makes

**Contact Voltage Rating:**

10.0 dc pounds per hour with retaining chain

**Contact Current Rating:**

1.0 milliamperes

**Phase Angle In Deg:**

15.0 and 20.0

**Dwell Time Rating In Deg:**

Between 43.0 and 47.0

**Plug In Mounting Feature:**

Not provided

**Base Connection Wiring Style:**

7 pin standard tube

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T320-k