NSN 5945-00-988-1609

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-988-1609

Thread Class: 2a single mounting facility **Thread Direction:** Right-hand single mounting facility **Overall Length:** 0.790 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.412 inches single mounting facility **Overall Height:** 1.245 inches **Overall Width:** 0.360 inches **Case Material:** Metal **Environmental Protection:** Hermetic **Fragility Factor:** Moderately rugged **Contact Material:** Silver **Contact Surface Treatment:** Gold **Frequency In Hertz:** 400.0 Winding Quantity: 1 **Purpose For Which Designed:** General **Coil Quantity:** 1 **Duty Type:** Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility Storage Type: General purpose warehouse **Cubic Measure:** 0.354 cubic inches Thready Qty Per Inch (tpi): 40 single mounting facility **Thread Size:** 0.112 inches single mounting facility

NSN 5945-00-988-1609

Electromagnetic Relay - Page 2 of 2



Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary **Time Delay:** 0.005 seconds fixed operate and release time **Operating Voltage Rating And Type At Specificationified Temp:** 115.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Precious Material And Location:** Contacts silver and contact surfaces gold **Precious Material:** Silver and gold **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 8 wire hook all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300