

View Online at <https://aerobasegroup.com/nsn/5945-00-988-1965>

Overall Length:

1.810 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.406 inches single mounting facility

Overall Diameter:

1.670 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.144 inches single mounting facility

Frequency In Hertz:

Between 45.0 and 420.0

Winding Quantity:

2

Coil Quantity:

1

Winding Dc Resistance Rating:

2.8 kilohms all windings

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Pile-up Main Contact Form Arrangement:

4c

Features Provided:

Polarized

Mounting Facility Pattern:

In-line single mounting facility

Time Delay:

0.01 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Coils are paralld connected

Terminal Type And Quantity:

14 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300