NSN 5945-00-988-6240

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-988-6240

| Overall Length: |
|---|
| 1.062 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.875 inches single mounting facility |
| Overall Height: |
| 1.793 inches |
| Overall Width: |
| 0.718 inches |
| Case Material: |
| Nickel |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.125 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Contact Material: |
| Silver |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 400.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 4.00= 11.1.1 |

1.367 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.005 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

NSN 5945-00-988-6240

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Precious Material And Location: Contacts silver Precious Material: Silver Terminal Type And Quantity: 8 wire hook all functions Shelf Life: N/a Unit Of Measure: -- Demilitarization:

No Fiig: A03300