NSN 5945-00-990-6830

Electromagnetic Relay - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5945-00-990-6830

| 2b single mounting facility |
|---|
| Thread Direction: |
| Right-hand single mounting facility |
| Overall Length: |
| 1.688 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.875 inches single mounting facility |
| Overall Height: |
| 1.344 inches |
| Overall Width: |
| 0.953 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic |
| Fragility Factor: |
| Moderately rugged |
| Contact Material: |
| Silver |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 237.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 2 threaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 2.162 cubic inches |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |

0.138 inches single mounting facility

NSN 5945-00-990-6830

Electromagnetic Relay - Page 2 of 2



Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action

Time Delay:

0.015 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 1.5 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 26.5 dc

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

_ ...

Demilitarization:

No

Fiig:

A03300