NSN 5945-00-993-5172

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-993-5172

Overall Length:

Between 1.250 inches and 1.310 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.190 inches single mounting facility and 1.210 inches single mounting facility

Overall Height:

Between 0.420 inches and 0.480 inches

Overall Width:

Between 0.770 inches and 0.830 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.115 inches single mounting facility and 0.135 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

•

Purpose For Which Designed:

General

Coil Quantity:

CO

Winding Dc Resistance Rating:

5.0 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.521 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

4.2 milliamperes dc single winding

Time Delay:

0.015 seconds fixed operate and release time

NSN 5945-00-993-5172

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac inductive load and 2.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

29.0 dc

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300