NSN 5945-00-995-1706

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-995-1706

Thread Class:
2a single mounting facility
Overall Length:
3.780 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.312 inches single mounting facility
Overall Height:
2.030 inches
Overall Width:
2.410 inches
Environmental Protection:
Hermetic
Frequency In Hertz:
60.0
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
145.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 threaded stud single mounting facility
Pile-up Main Contact Form Arrangement:
4c
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.138 inches single mounting facility
Mounting Facility Pattern:
Rectangular single mounting facility
Operating Current Rating And Type:
0.10 amperes ac single winding
Time Delay:
0.0200 seconds adjustable operate time and 0.0300 seconds adjustable operate time
Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

NSN 5945-00-995-1706

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 120.0 dc

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300