## NSN 5945-00-995-2428

Meter Movement Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-995-2428

| Terminal Quantity:  |
|---|
| 2   |
| Terminal Type:  |
| Pigtail   |
| Mounting Flange Width:  |
| 2.812 inches  |
| Case Material:  |
| Metal   |
| Environmental Protection:   |
| Explosion proof and hermetically sealed                                 |
| Mounting Configuration:   |
| Three no. 4-40 mtg studs spaced 120 degrees apart on a 1-1/4 in; radius |
| Voltage Rating:   |
| 125.0 volts   |
| Main Contact Arrangement:   |
| 1 pole, single throw, both positions maintained                         |
| Main Contact Current Type:  |
| Dc  |
| Main Contact Current Rating:  |
| 25.0 amperes  |
| Meter Movement Current Type:  |
| Dc  |
| Meter Movement Voltage In Volts:  |
| 50.000  |
| Meter Movement Current Range:   |
| +0.0/+50.0 microamperes   |
| Meter Mounting Type:  |
| Flush   |
| Contact Closing Condition:  |
| Decrease value  |
| Reset Facility Feature:   |
| Provided  |
| Meter Depth Behind Mounting Flange:                                     |
| 1.625 inches  |
| Meter Body Diameter:  |
| 2.125 inches  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
|   |

## NSN 5945-00-995-2428

Meter Movement Relay - Page 2 of 2

Fiig: T142-k

