

View Online at <https://aerobasegroup.com/nsn/5945-00-998-4872>

Overall Length:

3.734 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.687 inches single mounting facility

Overall Height:

2.532 inches

Overall Width:

3.305 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Frequency In Hertz:

60.0 or 400.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Operating Current Rating And Type:

200.0 milliamperes ac single winding

Time Delay:

0.05 seconds fixed release time

Auxiliary Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

25.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Special Features:

Non-pile-up main contact arrangement: 3 pole, single throw, normally open, double make; nonpile-up auxiliary contact arrangement: 1 pole, double throw, double break, double make

Terminal Type And Quantity:

12 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300