## NSN 5945-01-006-1410

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-006-1410

Overall Length:
0.810 inches
Overall Height:
0.230 inches
Overall Width:
0.210 inches
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
End Application:
Wsd: radar, series an/sps-4 (v); spruance class dd (963); los angeles class ssn (688); virginia class cgn (41); sturgeon class ssn (637);
forrestal class cv; landing craft air cushion (lcac); nimitz class cvn; ticonderoga class cg (47)
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
110.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.039 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Operating Voltage Rating And Type At Specificationified Temp:
4.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
250.0 milliamperes ac resistive load and 250.0 milliamperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
120.0 ac and 50.0 dc
Special Features:

6 pin all functions

Weapon system essential

Terminal Type And Quantity:

## NSN 5945-01-006-1410

Reed Relay - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300