NSN 5945-01-007-6797

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-007-6797

Overall Length:
0.810 inches
Overall Height:
0.510 inches
Overall Width:
0.410 inches
Environmental Protection:
Hermetic
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
1.2 kilohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Nonpile-up Main Contact Arrangement:
Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary
2 pole, double throw, one position momentary
2 pole, double throw, one position momentary Time Delay:
2 pole, double throw, one position momentaryTime Delay:0.006 seconds fixed operate and release time
 2 pole, double throw, one position momentary Time Delay: 0.006 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp:
 2 pole, double throw, one position momentary Time Delay: 0.006 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding
 2 pole, double throw, one position momentary Time Delay: 0.006 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
 2 pole, double throw, one position momentary Time Delay: 0.006 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 50.0 milliamperes dc resistive load
 2 pole, double throw, one position momentary Time Delay: 0.006 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 50.0 milliamperes dc resistive load Terminal Type And Quantity:
 2 pole, double throw, one position momentary Time Delay: 0.006 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 50.0 milliamperes dc resistive load Terminal Type And Quantity: 8 pin all functions
 2 pole, double throw, one position momentary Time Delay: 0.006 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 50.0 milliamperes dc resistive load Terminal Type And Quantity: 8 pin all functions Shelf Life:
2 pole, double throw, one position momentary Time Delay: 0.006 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 50.0 milliamperes dc resistive load Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a
2 pole, double throw, one position momentary Time Delay: 0.006 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 50.0 milliamperes dc resistive load Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a
2 pole, double throw, one position momentary Time Delay: 0.006 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 50.0 milliamperes dc resistive load Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:
2 pole, double throw, one position momentary Time Delay: 0.006 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 50.0 milliamperes dc resistive load Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:
2 pole, double throw, one position momentary Time Delay: 0.006 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 50.0 milliamperes dc resistive load Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure: Demilitarization: No