## NSN 5945-01-008-8327

Electromagnetic Relay - Page 1 of 2

1.875 inches single mounting facility

Overall Length: 2.250 inches

Overall Height: 3.688 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/5945-01-008-8327

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

| 2.250 inches  |
|---|
| Mounting Slot Width:                                    |
| 0.120 inches single mounting facility                   |
| Case Material:  |
| Plastic   |
| Environmental Protection:                               |
| Dustproof   |
| Fragility Factor:                                       |
| Moderately rugged                                       |
| Winding Quantity:                                       |
| 1   |
| Purpose For Which Designed:                             |
| General   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:                           |
| 120.0 ohms single winding                               |
| Duty Type:  |
| Continuous  |
| Arc Quenching Method:                                   |
| Air   |
| Mounting Facility Type And Quantity:                    |
| 2 slotted hole single mounting facility                 |
| Storage Type:   |
| General purpose warehouse                               |
| Features Provided:                                      |
| Polarized   |
| Cubic Measure:  |
| 5.063 cubic inches                                      |
| Mounting Facility Pattern:                              |
| In-line single mounting facility                        |
| Nonpile-up Main Contact Arrangement:                    |
| 2 pole, single throw, normally closed, momentary action |
| Operating Current Rating And Type:                      |
| 50.0 milliamperes dc single winding                     |
|   |
|   |

## NSN 5945-01-008-8327

Electromagnetic Relay - Page 2 of 2



| Time | Del | ay: |
|------|-----|-----|
|------|-----|-----|

0.04 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

6 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A03300