# NSN 5945-01-009-0154

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-009-0154

view Offiline at https://aerobasegroup.com/nsi//0340-01-003-0104
Thread Class:
2b second mounting facility
Thread Direction:
Right-hand second mounting facility
Overall Length:
3.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches second mounting facility
Overall Height:
6.230 inches
Overall Width:
3.090 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.199 inches first mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.500 inches second mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
6 unthreaded hole first mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
62.565 cubic inches
Thready Qty Per Inch (tpi):
32 second mounting facility
Thread Size:

Till Caa Oizc.

0.164 inches second mounting facility

# NSN 5945-01-009-0154

Electromagnetic Relay - Page 2 of 2



#### **Mounting Facility Pattern:**

Rectangular second mounting facility

#### **Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

#### Time Delay:

1.50 seconds adjustable release time and 15.00 seconds adjustable release time

#### **Nonpile-up Auxiliary Contact Arrangement:**

1 pole, double throw, one position momentary

#### **Auxiliary Contact Maximum Voltage Rating In Volts:**

480.0 ac

#### Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 15.0 amperes dc resistive load

## Main Contact Maximum Voltage Rating In Volts:

240.0 ac and 30.0 dc

#### **Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes ac resistive load

#### **Energizing Element Power Rating:**

8.0 watts

#### **Thread Series Designator:**

Unc second mounting facility

## **Terminal Type And Quantity:**

11 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

#### Demilitarization:

No

#### Fiig:

A03300