## NSN 5945-01-012-6646

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-012-6646

Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Thread Length:
0.312 inches single mounting facility
Overall Length:
1.109 inches
Overall Height:
1.593 inches
Overall Width:
0.859 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold flash
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
160.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
48 single mounting facility
Thread Size:
0.099 inches single mounting facility
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp
04.0 malta an OE de mare a calairea aireale minute a

24.0 volts ac 25 degrees celsius single winding

## NSN 5945-01-012-6646

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

120.0 ac and 30.0 dc

**Energizing Element Power Rating:** 

1.2 volts-amperes

**Precious Material And Location:** 

Contacts silver and contact surfaces gold

**Precious Material:** 

Silver and gold

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

14 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300