NSN 5945-01-012-6648



brochures, etc., that reflect specification type data in specification

| E | Electromagnetic Relay - Page 1 of 2 | |
|-----|---|-------------------|
| Vi | iew Online at https://aerobasegroup.com/nsn/5945-01-012-6648 | |
| 0 | verall Length: | |
| 1. | .730 inches | |
| 0 | verall Height: | |
| 2. | .140 inches | |
| 0 | verall Width: | |
| 1.: | .280 inches | |
| М | lounting Slot Width: | |
| 0. | 150 inches single mounting facility | |
| Er | nvironmental Protection: | |
| He | ermetic | |
| w | /inding Quantity: | |
| 1 | | |
| Co | oil Quantity: | |
| 1 | | |
| Di | uty Type: | |
| Co | ontinuous | |
| М | lounting Facility Type And Quantity: | |
| 3 : | slotted hole single mounting facility | |
| Fe | eatures Provided: | |
| Po | olarized | |
| М | lounting Facility Pattern: | |
| Tr | riangle single mounting facility | |
| No | onpile-up Main Contact Arrangement: | |
| 2 | pole, double throw, one position momentary | |
| Ti | ime Delay: | |
| 8. | .00 seconds fixed operate time | |
| Ce | enter To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: | |
| 1.4 | .446 inches single mounting facility | |
| 0 | perating Voltage Rating And Type At Specificationified Temp: | |
| 28 | 8.0 volts dc 25 degrees celsius single winding | |
| M | lain Contact Load Current Rating At Maximum Rated Voltage: | |
| 8. | .0 amperes ac resistive load and 8.0 amperes dc resistive load | |
| M | lain Contact Maximum Voltage Rating In Volts: | |
| 11 | 15.0 ac and 28.0 dc | |
| Τe | est Data Document: | |
| 81 | 1349-mil-r-83726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type | data in specifica |
| fo | ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type | data on certain |
| er | nvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | |
| Те | erminal Type And Quantity: | |
| 8 | pin all functions | |
| Sp | pecification Data: | |
| 81 | 1349-mil-r-83726/3 government specification | |

Shelf Life:

N/a

NSN 5945-01-012-6648

Electromagnetic Relay - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300

