## NSN 5945-01-013-0045

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-013-0045

| View Online at https://aerobasegroup.com/nsn/5945-01-013-0045   |
|---|
| Thread Class:   |
| 2b single mounting facility   |
| Overall Length:   |
| 2.625 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 0.750 inches single mounting facility   |
| Overall Height:   |
| 1.421 inches  |
| Overall Width:  |
| 1.125 inches  |
| Winding Quantity:   |
| 2   |
| Coil Quantity:  |
| 2   |
| Winding Dc Resistance Rating:   |
| 2.0 kilohms first winding   |
| Duty Type:  |
| Continuous  |
| Mounting Facility Type And Quantity:  |
| 2 threaded hole single mounting facility  |
| Features Provided:  |
| Polarized and latching contacts   |
| Thready Qty Per Inch (tpi):   |
| 32 single mounting facility   |
| Thread Size:  |
| 0.138 inches single mounting facility   |
| Mounting Facility Pattern:  |
| In-line single mounting facility  |
| Nonpile-up Main Contact Arrangement:  |
| 1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action |
| Time Delay:   |
| 0.025 seconds fixed operate and release time  |
| Operating Voltage Rating And Type At Specificationified Temp:   |
| 24.0 volts dc 25 degrees celsius all windings   |
| Main Contact Load Current Rating At Maximum Rated Voltage:  |
| 20.0 amperes dc resistive load  |
| Main Contact Maximum Voltage Rating In Volts:   |
| 28.0 dc   |
| Thread Series Designator:   |
| Unc single mounting facility  |

8 pin all functions

**Terminal Type And Quantity:** 

## NSN 5945-01-013-0045

Electromagnetic Relay - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300