NSN 5945-01-015-1554

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-015-1554 **Overall Length:** 0.810 inches **Overall Height:** 0.410 inches **Overall Width:** 0.410 inches **Environmental Protection:** Salt spray resistant and humidity proof **Contact Material:** Silver **Contact Surface Treatment:** Gold **Winding Quantity: Coil Quantity:** Winding Dc Resistance Rating: 60.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 plug-in terminal single mounting facility **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary Time Delay: 0.004 seconds fixed operate and release time Operating Voltage Rating And Type At Specificationified Temp: 6.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 milliamperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Precious Material And Location:** Contacts silver and contact surfaces gold **Precious Material:** Gold and silver **Terminal Type And Quantity:** 8 pin all functions Shelf Life: N/a

Unit Of Measure:

NSN 5945-01-015-1554

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300