NSN 5945-01-016-0558

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-016-0558

Thread Class:
2b second mounting facility
Thread Direction:
Right-hand second mounting facility
Overall Length:
3.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches second mounting facility
Overall Height:
4.520 inches
Overall Width:
3.090 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.199 inches first mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.500 inches second mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
6 unthreaded hole first mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
45.392 cubic inches
Thready Qty Per Inch (tpi):
32 second mounting facility
Thread Size:
0.164 inches second mounting facility

NSN 5945-01-016-0558

Electromagnetic Relay - Page 2 of 2



Mounting Facility Pattern: Rectangular second mounting facility **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary Time Delay: 5.00 seconds adjustable operate time and 50.00 seconds adjustable operate time **Operating Voltage Rating And Type At Specificationified Temp:** 32.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 15.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 240.0 ac and 30.0 dc **Energizing Element Power Rating:** 8.0 watts **Special Features:** Transparent tamperproof cover **Thread Series Designator:** Unc second mounting facility **Terminal Type And Quantity:** 8 screw all functions Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A03300