

View Online at <https://aerobasegroup.com/nsn/5945-01-016-7349>

Overall Length:

4.343 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.687 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility

Overall Height:

3.956 inches

Overall Width:

4.156 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Operating Current Rating And Type:

600.0 milliamperes dc single winding

Time Delay:

0.040 seconds fixed release time

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

150.0 amperes ac resistive load and 150.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A03300

Mil-std (military Standard):

Mil-prf-6106 spec.