## NSN 5945-01-016-7349

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-016-7349

g
Overall Length:
4.343 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.687 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.500 inches single mounting facility
Overall Height:
3.956 inches
Overall Width:
4.156 inches
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.218 inches single mounting facility
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Mounting Facility Pattern:
Rectangular single mounting facility
Operating Current Rating And Type:
600.0 milliamperes dc single winding
Time Delay:
0.040 seconds fixed release time
Auxiliary Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
150.0 amperes ac resistive load and 150.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

## NSN 5945-01-016-7349

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300

Mil-std (military Standard):

Mil-prf-6106 spec.