NSN 5945-01-016-9836

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-016-9836

Overall Length:
2.188 inches
Overall Height:
3.500 inches
Overall Width:
3.250 inches
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Purpose For Which Designed:
General
Duty Type:
Continuous
Pile-up Main Contact Form Arrangement:
r no up main contact r onn / trangemont.
4g
4g
4g Storage Type:
4g Storage Type: General purpose warehouse
4g Storage Type: General purpose warehouse Operating Voltage Rating And Type At Specificationified Temp:
4g Storage Type: General purpose warehouse Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts ac 25 degrees celsius single winding
4g Storage Type: General purpose warehouse Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts ac 25 degrees celsius single winding Main Contact Maximum Voltage Rating In Volts:
4g Storage Type: General purpose warehouse Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts ac 25 degrees celsius single winding Main Contact Maximum Voltage Rating In Volts: 24.0 ac
4g Storage Type: General purpose warehouse Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts ac 25 degrees celsius single winding Main Contact Maximum Voltage Rating In Volts: 24.0 ac Shelf Life:
4g Storage Type: General purpose warehouse Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts ac 25 degrees celsius single winding Main Contact Maximum Voltage Rating In Volts: 24.0 ac Shelf Life: N/a
4g Storage Type: General purpose warehouse Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts ac 25 degrees celsius single winding Main Contact Maximum Voltage Rating In Volts: 24.0 ac Shelf Life: N/a
4g Storage Type: General purpose warehouse Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts ac 25 degrees celsius single winding Main Contact Maximum Voltage Rating In Volts: 24.0 ac Shelf Life: N/a Unit Of Measure:

A03300