

View Online at <https://aerobasegroup.com/nsn/5945-01-018-1934>

Thread Class:

2b second mounting facility

Thread Direction:

Right-hand second mounting facility

Overall Length:

3.380 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches second mounting facility

Overall Height:

7.480 inches

Overall Width:

3.090 inches

Case Material:

Plastic

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.199 inches first mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches second mounting facility

Fragility Factor:

Moderately rugged

Frequency In Hertz:

60.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole first mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

78.123 cubic inches

Thready Qty Per Inch (tpi):

32 second mounting facility

Thread Size:

0.164 inches second mounting facility

Mounting Facility Pattern:

Rectangular second mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

2.00 seconds adjustable release time and 20.00 seconds adjustable release time

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 15.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

240.0 ac and 30.0 dc

Energizing Element Power Rating:

8.0 watts

Thread Series Designator:

Unc second mounting facility

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300