## NSN 5945-01-019-5521

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-019-5521

| Overall Length:   |
|---|
| 2.250 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.844 inches single mounting facility                                     |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.438 inches single mounting facility                                     |
| Overall Height:   |
| 2.609 inches  |
| Overall Width:  |
| 1.906 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.150 inches single mounting facility                                     |
| Frequency In Hertz:   |
| Between 50.0 and 60.0   |
| Winding Quantity:   |
| 1   |
| Coil Quantity:  |
| 1   |
| Duty Type:  |
| Continuous  |
| Mounting Facility Type And Quantity:                                      |
| 2 unthreaded hole single mounting facility                                |
| Mounting Facility Pattern:  |
| Diagonal single mounting facility   |
| Nonpile-up Main Contact Arrangement:                                      |
| 2 pole, single throw, normally open, momentary action                     |
| Time Delay:   |
| 0.014 seconds fixed operate and release time                              |
| Operating Voltage Rating And Type At Specificationified Temp:             |
| 110.0 volts ac 25 degrees celsius single winding                          |
| Main Contact Load Current Rating At Maximum Rated Voltage:                |
| 10.0 amperes ac resistive load  |
| Main Contact Maximum Voltage Rating In Volts:                             |
| 300.0 ac  |
| Terminal Type And Quantity:   |
| 6 pin all functions   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5945-01-019-5521

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300