

<b>NSN 5945-01-019-6922</b> Electromagnetic Relay - Page 1 of 2	Aer
View Online at https://aerobasegroup.com/nsn/5945-01-019-6922	
Overall Length:	
1.491 inches	
Center To Center Distance Between Mounting Facilities Parallel To Length:	
1.200 inches single mounting facility	
Overall Height:	
0.455 inches	
Overall Width:	
1.460 inches	
Case Material:	
Metal	
Environmental Protection:	
Hermetic	
Unthreaded Mounting Hole Diameter:	
0.121 inches single mounting facility	
Fragility Factor:	
Moderately rugged	
Winding Quantity:	
1	
Purpose For Which Designed:	
General	
Coil Quantity:	
1	
Winding Dc Resistance Rating:	
2.5 kilohms single winding	
Duty Type:	

Continuous

**Arc Quenching Method:** 

Air

**Mounting Facility Type And Quantity:** 

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

**Cubic Measure:** 

0.990 cubic inches

**Mounting Facility Pattern:** 

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:** 

2 pole, double throw, one position momentary

**Operating Current Rating And Type:** 

8.0 milliamperes dc single winding

Time Delay:

0.015 seconds fixed operate time

# NSN 5945-01-019-6922

Electromagnetic Relay - Page 2 of 2



### Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

# **Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

#### **Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

8 wire hook all functions

#### **Specification Data:**

81349-mil-r-5757/13 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

\_

**Demilitarization:** 

No

Fiig:

A03300