

View Online at <https://aerobasegroup.com/nsn/5945-01-020-6263>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

Between 1.844 inches and 1.906 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.344 inches single mounting facility and 1.406 inches single mounting facility

Overall Height:

Between 3.156 inches and 3.218 inches

Overall Width:

Between 1.844 inches and 1.906 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

230.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

11.690 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.04 seconds fixed operate time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.406 inches single mounting facility and 1.468 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load and 15.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300