# NSN 5945-01-022-6814

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-022-6814

#### **Overall Length:**

5.220 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.812 inches single mounting facility

#### **Overall Height:**

1.520 inches

#### **Overall Width:**

2.190 inches

**Environmental Protection:** 

Hermetic

**Unthreaded Mounting Hole Diameter:** 

0.170 inches single mounting facility

#### Winding Quantity:

1

# Coil Quantity:

1

Winding Dc Resistance Rating:

190.0 ohms single winding

Duty Type:

Continuous

#### Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

#### Mounting Facility Pattern:

Rectangular single mounting facility

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### **Operating Current Rating And Type:**

88.0 milliamperes ac single winding

#### Time Delay:

0.375 seconds fixed operate time and 3.00 seconds fixed operate time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

120.0 volts ac 25 degrees celsius single winding

# Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac inductive load

# Main Contact Maximum Voltage Rating In Volts:

120.0 ac

### **Special Test Features:**

Navord od41152

### Terminal Type And Quantity:

8 wire hook all functions

# NSN 5945-01-022-6814

Electromagnetic Relay - Page 2 of 2



# **Reference Number Differentiating Characteristics:**

As differentiated by special test features

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

Fiig:

A03300