NSN 5945-01-024-3827

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-024-3827

Overall Length:800.000 inchesOverall Height:1.100 inchesOverall Width:0.400 inchesEnvironmental Protection:HermeticWinding Quantity:1Coil Quantity:1Winding Dc Resistance Rating:500.0 ohms single windingDuty Type:ContinuousOperating Voltage Rating And Type At Specificationified Temp:26.0 volts dc 25 degrees celsius single windingMain Contact Load Current Rating At Maximum Rated Voltage:1.0 amperes ac resistive load and 1.0 amperes dc resistive loadMain Contact Maximum Voltage Rating In Volts:115.0 ac and 26.5 dc
Overall Height: 1.100 inches Overall Width: 0.400 inches Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
 1.100 inches Overall Width: 0.400 inches Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Minding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Overall Width: 0.400 inches Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
0.400 inches Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Hermetic Winding Quantity: 1 Coil Quantity: 1 Minding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Winding Quantity: Coil Quantity: Coil Quantity: Minding Dc Resistance Rating: S00.0 ohms single winding Duty Type: Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
1 Coil Quantity: 1 Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Coil Quantity: 1 Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
1Winding Dc Resistance Rating:500.0 ohms single windingDuty Type:ContinuousOperating Voltage Rating And Type At Specificationified Temp:26.0 volts dc 25 degrees celsius single windingMain Contact Load Current Rating At Maximum Rated Voltage:1.0 amperes ac resistive load and 1.0 amperes dc resistive loadMain Contact Maximum Voltage Rating In Volts:
 Winding Dc Resistance Rating: 500.0 ohms single winding Duty Type: Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
 500.0 ohms single winding Duty Type: Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Duty Type: Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Continuous Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Operating Voltage Rating And Type At Specificationified Temp: 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
 26.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
1.0 amperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts:
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 26.5 dc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03300