

View Online at <https://aerobasegroup.com/nsn/5945-01-026-1225>

Overall Length:

1.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

1.270 inches

Overall Width:

1.015 inches

Mounting Slot Width:

0.150 inches single mounting facility

Environmental Protection:

Dustproof

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

290.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

Features Provided:

Polarized

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

120.0 milliamperes dc single winding

Time Delay:

0.018 seconds fixed release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.421 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Terminal Type And Quantity:

14 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300