NSN 5945-01-026-1228

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-026-1228

| Thread Class: |
|--|
| 2a single mounting facility |
| Thread Direction: |
| Right-hand single mounting facility |
| Overall Length: |
| 1.797 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.250 inches single mounting facility |
| Overall Height: |
| 3.063 inches |
| Overall Width: |
| 1.672 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 70.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 9.023 cubic inches |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |
| 0.164 inches single mounting facility |

Mounting Facility Pattern:
Triangle single mounting facility

NSN 5945-01-026-1228

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.250 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load and 15.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300