NSN 5945-01-027-6908

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-027-6908
Overall Length:
1.320 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.078 inches single mounting facility
Overall Height:
0.600 inches
Overall Width:
0.410 inches
Unthreaded Mounting Hole Diameter:
0.120 inches single mounting facility
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
40.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.01 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
6.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
300.0 amperes ac resistive load and 300.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Test Data Document:
81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 pin all functions
Specification Data:
81349-mil-r-39016/16 government specification

N/a

Shelf Life:

Unit Of Measure:

NSN 5945-01-027-6908

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300