

View Online at <https://aerobasegroup.com/nsn/5945-01-028-0508>

Overall Length:

1.340 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.062 inches single mounting facility

Overall Height:

1.062 inches

Overall Width:

0.400 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.120 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

975.0 ohms all windings

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Features Provided:

Polarized and latching contacts

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.01 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

150.0 amperes ac resistive load and 150.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 pin all functions

Specification Data:

81349-mil-r-39016/32 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300