NSN 5945-01-028-2652

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-028-2652

| Overall Length: |
|---|
| 1.180 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches single mounting facility |
| Overall Height: |
| 0.612 inches |
| Overall Width: |
| 0.410 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.096 inches single mounting facility |
| Winding Quantity: |
| 2 |
| Coil Quantity: |
| 2 |
| Winding Dc Resistance Rating: |
| 1.0 kilohms all windings |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Features Provided: |
| Polarized and latching contacts |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Time Delay: |
| 0.01 seconds fixed operate and release time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 26.5 volts dc 25 degrees celsius all windings |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 2.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Terminal Type And Quantity: |
| 10 pin all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5945-01-028-2652

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300