NSN 5945-01-029-3559

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-029-3559

| Body Style: |
|---|
| Enclosed frame |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| Between 1.917 inches and 1.927 inches |
| Body Diameter: |
| 1.510 centimeters |
| Body Length: |
| 2.030 inches |
| Case Material: |
| Metal |
| Unthreaded Mounting Hole Diameter: |
| Between 0.194 inches and 0.208 inches |
| Connector Manufacturer Code: |
| 30003 |
| Connector Manufacturer Part Number: |
| 537as721 |
| Fragility Factor: |
| Moderately rugged |
| Actuator Width: |
| Between 0.115 inches and 0.155 inches |
| End Application: |
| 1005-01-048-3956 pick off unit |
| Inclosure Type: |
| Fully enclosed |
| Magnetic Coil Quantity: |
| 1 |
| Electrical Resistance: |
| Between 2.85 ohms and 3.15 ohms |
| Duty Type: |
| Intermittent |
| Terminal Location: |
| One side |
| Voltage Rating In Volts: |
| Between 20.0 dc and 30.0 dc |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 8.143 cubic inches |
| Actuator Stroke Type: |
| Pull |

NSN 5945-01-029-3559

Electrical Solenoid - Page 2 of 2



| Linear Force Delivered: |
|--------------------------------|
| 5.00 pounds |
| Power Takeoff Connection Type: |
| Flatted-drilled |
| Mounting Facility Pattern: |
| Two position in-line |
| Terminal Type And Quantity: |
| 1 connector, receptacle |
| Fsc Application Data: |
| Guns, through 30mm |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A134a0