

View Online at <https://aerobasegroup.com/nsn/5945-01-030-6071>

**Overall Length:**

1.718 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.625 inches single mounting facility

**Overall Height:**

1.395 inches

**Overall Width:**

1.025 inches

**Mounting Slot Width:**

0.150 inches single mounting facility

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

70.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 slotted hole single mounting facility

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Time Delay:**

0.015 seconds fixed release time

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.446 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

15.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

208.0 ac and 28.0 dc

**Special Test Features:**

Mil-0-21549b-sp24-1

**Terminal Type And Quantity:**

14 pin all functions

**Reference Number Differentiating Characteristics:**

Special test features

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-0-21549 spec.