NSN 5945-01-031-1324

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-031-1324

view Online at https://aerobasegroup.com/nsn/5945-01-031-1324
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.672 inches single mounting facility and 0.702 inches single mounting facility
Overall Height:
2.140 inches
Overall Width:
1.000 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Contact Material:
Silver and platinum
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
8.0 kilohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 threaded stud single mounting facility
Cubic Measure:
2.140 cubic inches
Thready Qty Per Inch (tpi):
40 single mounting facility
Thread Size:
0.112 inches single mounting facility
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Current Rating And Type:
3.5 milliamperes dc single winding
Time Delay:

Time Delay

0.015 seconds fixed operate time

NSN 5945-01-031-1324

Electromagnetic Relay - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

0.672 inches single mounting facility and 0.702 inches single mounting facility

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Precious Material And Location:

Contacts palladium and contacts silver

Precious Material:

Palladium and silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300