

View Online at <https://aerobasegroup.com/nsn/5945-01-032-1031>

Overall Length:

6.230 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.880 inches single mounting facility

Overall Height:

3.090 inches

Overall Width:

3.250 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.199 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

6 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

20.00 seconds adjustable release time and 200.00 seconds adjustable release time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes ac resistive load and 1.0 amperes dc resistive load

Energizing Element Power Rating:

8.0 watts

Terminal Type And Quantity:

11 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300