NSN 5945-01-033-1310

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-033-1310

view Offilite at https://defobasegroup.com/nsi//0940-01-000-1010
Overall Length:
6.230 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.750 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.880 inches single mounting facility
Overall Height:
3.090 inches
Overall Width:
3.250 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.199 inches single mounting facility
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 6 unthreaded hole single mounting facility
6 unthreaded hole single mounting facility
6 unthreaded hole single mounting facility Storage Type:
6 unthreaded hole single mounting facility Storage Type: General purpose warehouse
6 unthreaded hole single mounting facility Storage Type: General purpose warehouse Cubic Measure:
6 unthreaded hole single mounting facility Storage Type: General purpose warehouse Cubic Measure: 62.564 cubic inches
6 unthreaded hole single mounting facility Storage Type: General purpose warehouse Cubic Measure: 62.564 cubic inches Mounting Facility Pattern:
6 unthreaded hole single mounting facility Storage Type: General purpose warehouse Cubic Measure: 62.564 cubic inches Mounting Facility Pattern: Rectangular single mounting facility

3.00 minutes adjustable operate time and 30.00 minutes adjustable operate time

NSN 5945-01-033-1310

Electromagnetic Relay - Page 2 of 2



Nonpile-up Auxiliary Contact Arrangement:

1 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Terminal Type And Quantity:

11 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300