## NSN 5945-01-033-2309

Electromagnetic Relay - Page 1 of 2

**Thread Class:** 

**Thread Direction:** 

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-01-033-2309

| Right-hand single mounting facility  |
|--|
| Overall Length:  |
| 0.950 inches   |
| Overall Height:  |
| 1.397 inches   |
| Overall Width:   |
| 0.735 inches   |
| Case Material:   |
| Plastic  |
| Environmental Protection:  |
| Dustproof  |
| Fragility Factor:  |
| Moderately rugged  |
| Contact Material:  |
| Silver   |
| Winding Quantity:  |
| 1  |
| Purpose For Which Designed:  |
| General  |
| Coil Quantity:   |
| 1  |
| Winding Dc Resistance Rating:  |
| 700.0 ohms single winding  |
| Duty Type:   |
| Continuous   |
| Arc Quenching Method:  |
| Air  |
| Mounting Facility Type And Quantity:   |
|  |
| 1 threaded stud single mounting facility   |
| 1 threaded stud single mounting facility  Storage Type:  |
|  |
| Storage Type:  |
| Storage Type: General purpose warehouse  |
| Storage Type: General purpose warehouse Cubic Measure:   |
| Storage Type: General purpose warehouse Cubic Measure: 0.975 cubic inches  |
| Storage Type: General purpose warehouse Cubic Measure: 0.975 cubic inches Thready Qty Per Inch (tpi):  |
| Storage Type: General purpose warehouse Cubic Measure: 0.975 cubic inches Thready Qty Per Inch (tpi): 48 single mounting facility  |
| Storage Type: General purpose warehouse Cubic Measure: 0.975 cubic inches Thready Qty Per Inch (tpi): 48 single mounting facility Thread Size:                                       |
| Storage Type: General purpose warehouse Cubic Measure: 0.975 cubic inches Thready Qty Per Inch (tpi): 48 single mounting facility Thread Size: 0.099 inches single mounting facility |

## NSN 5945-01-033-2309

Electromagnetic Relay - Page 2 of 2



## **Operating Voltage Rating And Type At Specificationified Temp:**

115.0 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

7.5 amperes ac resistive load and 7.5 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Precious Material And Location:** 

Contacts silver

**Precious Material:** 

Silver

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

8 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300