NSN 5945-01-033-3922

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-033-3922

Overall Length:
1.180 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.125 inches single mounting facility
Overall Height:
1.100 inches
Overall Width:
0.400 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.096 inches single mounting facility
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
4.0 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.519 cubic inches
Mounting Facility Pattern:
Diagonal single mounting facility
Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

NSN 5945-01-033-3922

Electromagnetic Relay - Page 2 of 2



Time [Delay:
--------	--------

0.015 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300