
NSN 5945-01-035-3879

Electromagnetic Relay - Page 1 of 2





Overall Length:

2.406 inches

Overall Diameter:

1.500 inches

Unthreaded Mounting Hole Diameter:

0.144 inches single mounting facility

Frequency In Hertz:

400.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

3.5 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 unthreaded hole single mounting facility

Features Provided:

Polarized

Mounting Facility Pattern:

Ciruclar single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

100.0 milliamperes ac single winding

Time Delay:

0.015 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

117.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

2000.0 ac

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5945-01-035-3879

Electromagnetic Relay - Page 2 of 2

Fiig: A03300

