## NSN 5945-01-037-6432

Electromagnetic Relay - Page 1 of 2

115.0 volts ac 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

1.5 amperes ac motor load and 1.5 amperes dc motor load

Overall Length: 2.187 inches



View Online at https://aerobasegroup.com/nsn/5945-01-037-6432

Center To Center Distance Between Mounting Facilities Parallel To Length:
1.844 inches single mounting facility
Overall Height:
2.094 inches
Overall Width:
0.687 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.147 inches single mounting facility
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Winding Quantity:
2
Coil Quantity:
2
Winding Dc Resistance Rating:
1.6 kilohms all windings
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Latching contacts
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.02 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:

## NSN 5945-01-037-6432

Electromagnetic Relay - Page 2 of 2



## Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Precious Material And Location:** 

Terminal surfaces gold

Precious Material:

Gold

**Terminal Type And Quantity:** 

10 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300