NSN 5945-01-037-8516

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-037-8516

| Overall Law with |
|---|
| Overall Length: |
| 1.015 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.625 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.446 inches single mounting facility |
| Overall Height: |
| 1.000 inches |
| Overall Width: |
| 1.015 inches |
| Environmental Protection: |
| Corrosion resistant and fungus proof and vibration resistant and shock resistant and hermetic |
| Frequency In Hertz: |
| Between 60.0 and 400.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 threaded hole single mounting facility |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 3 pole, single throw, normally open, momentary action and 1 pole, double throw, two positions momentary |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 115.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 12.0 amperes dc inductive load and 15.0 amperes ac inductive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 200.0 ac and 28.0 dc |
| Precious Material And Location: |
| Terminals gold |
| Precious Material: |
| Gold |
| Terminal Type And Quantity: |
| 9 pin contacts |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5945-01-037-8516

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300