## NSN 5945-01-039-7369

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-039-7369

<ul> <li>1.718 inches</li> <li>Overall Weight:</li> <li>1.290 inches</li> <li>Overall Width:</li> <li>1.025 inches</li> <li>Mounting Slot Width:</li> <li>0.150 inches single mounting facility</li> <li>Winding Quantity:</li> <li>1</li> <li>Coll Quantity:</li> <li>1</li> <li>Duty Type:</li> <li>Continuous</li> <li>Mounting Facility Type And Quantity:</li> <li>3 slotted hole single mounting facility</li> <li>Features Provided:</li> <li>Polorized</li> <li>Polarized</li> <li>Mounting Facility Pattern:</li> <li>Triangle single mounting facility</li> <li>Nonpile-up Main Contact Arrangement:</li> <li>4 pole, double throw, one position momentary</li> <li>Operating Current Rating And Type:</li> <li>80.0 milliamperes da single winding</li> <li>Time Delay:</li> <li>0.015 seconds fixed operate and release time</li> <li>Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle</li> <li>4.446 inches single mounting facility</li> <li>Operating Voltage Rating And Type At Specificationified Temp:</li> <li>48.0 volts da 25 degrees celsius single winding</li> <li>14.00 amperes ac resistive load and 10.0 amperes da resistive load</li> <li>Main Contact Maximum Nottage Rating In Volts:</li> <li>11.5.0 as and 28.0 de</li> <li>Termina Type And Quantity:</li> <li>14 pin all functions</li> <li>Shelf Life:</li> <li>N/a</li> <li>Unit Of Measure:</li> </ul>	Overall Leng	tn:
1.290 Inches Overall Width: 1.025 Inches Mounting Slot Width: 1.025 Inches Mounting Slot Width: 1.025 Inches single mounting facility Winding Quantity: 1 Coll Quantity: 1 Coll Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 3 Isoted hole single mounting facility Features Provided: Polarized Mounting Facility Patern: Triangle single mounting facility Nopple-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 80.0 milliamperes de single winding Time Delay: 0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 Inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts de 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes de resistive load Main Contact Load Current Rating At Maximum Rated Voltage: 115.0 act and 28.0 de Terminal Type And Quantity: 14 pin all functions Sheft Life: Na		
Overall Width:         1.025 inches         Mounting Slot Width:         0.150 inches single mounting facility         Winding Quantity:         1         Coll Quantity:         1         Duty Type:         Continuous         Mounting Facility Type And Quantity:         3 slotted hole single mounting facility         Features Provided:         Polarized         Mounting Facility Pattern:         Triangle single mounting facility         Nopel-up Main Contact Arrangement:         4 pole, double throw, one position momentary         Operating Current Rating And Type:         80.0 millamperes da single winding         Time Delay:         0.015 seconds fixed operate and release time         Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle         1.446 inches single mounting facility         Operating Voltage Rating And Type At Specificationified Temp:         4.80 volts da 25 degrees celsius single winding         Min Contact Load Current Rating At Maximum Rated Voltage:         10.0 amperes ac resistive load and 10.0 amperes da resistive load         Main Contact Maximum Voltage Rating In Volts:         15.0 ac and 28.0 do:         Terminal Type And Quantity:	-	ht:
1.225 inches         Mounting Slot Width:         0.150 inches single mounting facility         Winding Quantity:         1         Coil Quantity:         1         Duty Type:         Continuous         Mounting Facility Type And Quantity:         3 slotted hole single mounting facility         Features Provided:         Polarized         Mounting Facility Pattern:         Triangle single mounting facility         Nong Facility Pattern:         Triangle single mounting facility         Nonger and the single mounting facility         Nonger and the single mounting facility         Nonger and the single mounting facility         Nongile-up Main Contact Arrangement:         4 pole, double throw, one position momentary         Operating Current Rating And Type:         8.0.0 millitamperes dc single winding         Time Delay:         0.015 seconds fixed operate and release time         Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle         1.446 inches single mounting facility         Operating Voltage Rating And Type Al Specificationified Temp:         4.80 volts dc 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltag		
Mounting Slot Width:         0.150 inches single mounting facility         Winding Quantity:         1         Coil Quantity:         1         Duty Type:         Continuous         Mounting Facility Type And Quantity:         3 slotted hole single mounting facility         Features Provided:         Polarized         Mounting Facility Pattern:         Triangle single mounting facility         Nonpile-up Main Contact Arrangement:         4 pole, double throw, one position momentary         Operating Current Rating And Type:         8.0 on milliamperes de single winding         Time Delay:         0.015 seconds fixed operate and release time         Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle         1.446 inches single mounting facility         Operating Voltage Rating And Type At Specificationified Temp:         4.450 volts de 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         10.0 amperes ac resistive load and 10.0 amperes de resistive load         Main Contact Load Current Rating At Maximum Rated Voltage:         15.0 ac and 28.0 do:         Terminal Type And Quantity:         14 pin all functions		h:
0.150 inches single mounting facility Winding Quantity: 1 Coll Quantity: 1 Coll Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 3 stotted hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Triangle single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 80.0 milliamperes dc single winding Time Delay: 0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 linches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Maximum Notage Rating In Volts: 11.0.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Sheff Life: Na		
Winding Quantity: 1 Coll Quantity: 1 Coll Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 3 slotted hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Triangle single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 80.0 milliamperes dc single winding Time Delay: 0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 linches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Sheft Life: N/a	-	
1         Coil Quantity:         1         Duty Type:         Continuous         Mounting Facility Type And Quantity:         3 slotted hole single mounting facility         Features Provided:         Polarized         Mounting Facility Pattern:         Triangle single mounting facility         Nopile-up Main Contact Arrangement:         4 pole, double throw, one position momentary         Operating Current Rating And Type:         80.0 milliamperes dc single winding         Time Delay:         0.015 seconds fixed operate and release time         Center D Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle         1.446 inches single mounting facility         Operating Voltage Rating And Type At Specificationified Temp:         4.80. volts dc 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         10.0 amperes ac resistive load and 10.0 amperes dc resistive load         Main Contact Maximum Voltage Rating In Volts:         115.0 ac and 28.0 dc         Terminal Type And Quantity:         14 pin all functions         Shelf Life:         Na		
Coll Quantity:         1         Duty Type:         Continuous         Mounting Facility Type And Quantity:         3 slotted hole single mounting facility         Features Provided:         Polarized         Mounting Facility Pattern:         Triangle single mounting facility         Nopile-up Main Contact Arrangement:         4 pole, double throw, one position momentary         Operating Current Rating And Type:         80.0 milliamperes do single winding         Time Delay:         0.015 seconds fixed operate and release time         Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle         1.446 inches single mounting facility         Operating Voltage Rating And Type At Specificationified Temp:         4.80 volts do 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         10.0 amperes ac resistive load and 10.0 amperes dc resistive load         Main Contact Maximum Voltage Rating In Volts:         115.0 ac and 28.0 dc         Terminal Type And Quantity:         14 pin all functions         Shelf Life:         N/a	-	intity:
1         Duty Type:         Continuous         Mounting Facility Type And Quantity:         3 slotted hole single mounting facility         Features Provided:         Polarized         Mounting Facility Pattern:         Triangle single mounting facility         Nopple-up Main Contact Arrangement:         4 pole, double throw, one position momentary         Operating Current Rating And Type:         80.0 milliamperes dc single winding         Time Delay:         0.015 seconds fixed operate and release time         Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle         1.446 inches single mounting facility         Operating Voltage Rating And Type At Specificationified Temp:         4.80. volts dc 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         10.0 amperes ac resistive load and 10.0 amperes dc resistive load         Main Contact Maximum Voltage Rating In Volts:         115.0 ac and 28.0 dc         Terminal Type And Quantity:         14 pin all functions         Shelf Life:         N/a		
Duty Type:         Continuous         Mounting Facility Type And Quantity:         3 slotted hole single mounting facility         Features Provided:         Polarized         Mounting Facility Pattern:         Triangle single mounting facility         Nonpile-up Main Contact Arrangement:         4 pole, double throw, one position momentary         Operating Current Rating And Type:         80.0 milliamperes dc single winding         Time Delay:         0.015 seconds fixed operate and release time         Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle         1.446 inches single mounting facility         Operating Voltage Rating And Type At Specificationified Temp:         4.80. volts dc 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         10.0 amperes ac resistive load and 10.0 amperes dc resistive load         Main Contact Maximum Voltage Rating In Volts:         115.0 ac and 28.0 dc         Terminal Type And Quantity:         14 pin all functions         Shelf Life:         Na	Coil Quantity	/:
Continuous Mounting Facility Type And Quantity: 3 slotted hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Triangle single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 80.0 milliamperes dc single winding Time Delay: 0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a		
Mounting Facility Type And Quantity:         3 slotted hole single mounting facility         Features Provided:         Polarized         Mounting Facility Pattern:         Triangle single mounting facility         Nonpile-up Main Contact Arrangement:         4 pole, double throw, one position momentary         Operating Current Rating And Type:         80.0 milliamperes dc single winding         Time Delay:         0.015 seconds fixed operate and release time         Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle         1.446 inches single mounting facility         Operating Voltage Rating And Type At Specificationified Temp:         48.0 volts dc 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         10.0 amperes ac resistive load and 1.0.0 amperes dc resistive load         Main Contact Maximum Voltage Rating In Volts:         115.0 ac and 28.0 dc         Terminal Type And Quantity:         14 pin all functions         Sheff Life:         N/a	Duty Type:	
3 slotted hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Triangle single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 80.0 milliamperes dc single winding Time Delay: 0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Sheff Life: N/a	Continuous	
Features Provided:         Polarized         Mounting Facility Pattern:         Triangle single mounting facility         Nonpile-up Main Contact Arrangement:         4 pole, double throw, one position momentary         Operating Current Rating And Type:         80.0 milliamperes dc single winding         Time Delay:         0.015 seconds fixed operate and release time         Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle         1.446 inches single mounting facility         Operating Voltage Rating And Type At Specificationified Temp:         48.0 volts dc 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         10.0 amperes ac resistive load and 10.0 amperes dc resistive load         Main Contact Maximum Voltage Rating In Volts:         115.0 ac and 28.0 dc         Terminal Type And Quantity:         14 pin all functions         Shelf Life:         N/a	Mounting Fa	cility Type And Quantity:
Polarized         Mounting Facility Pattern:         Triangle single mounting facility         Nonpile-up Main Contact Arrangement:         4 pole, double throw, one position momentary         Operating Current Rating And Type:         80.0 milliamperes dc single winding         Time Delay:         0.015 seconds fixed operate and release time         Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle         1.446 inches single mounting facility         Operating Voltage Rating And Type At Specificationified Temp:         48.0 volts dc 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         10.0 amperes ac resistive load and 10.0 amperes dc resistive load         Main Contact Maximum Voltage Rating In Volts:         15.0 ac and 28.0 dc         Terminal Type And Quantity:         14 pin all functions         Shelf Life:         N/a	3 slotted hole	single mounting facility
Mounting Facility Pattern:         Triangle single mounting facility         Nonpile-up Main Contact Arrangement:         4 pole, double throw, one position momentary         Operating Current Rating And Type:         80.0 milliamperes dc single winding         Time Delay:         0.015 seconds fixed operate and release time         Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle         1.446 inches single mounting facility         Operating Voltage Rating And Type At Specificationified Temp:         48.0 volts dc 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         10.0 amperes ac resistive load and 10.0 amperes dc resistive load         Main Contact Maximum Voltage Rating In Volts:         15.0 ac and 28.0 dc         Terminal Type And Quantity:         14 pin all functions         Shelf Life:         N/a		vided:
Triangle single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 80.0 milliamperes dc single winding Time Delay: 0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a	Polarized	
Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 80.0 milliamperes dc single winding Time Delay: 0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a	Mounting Fa	cility Pattern:
4 pole, double throw, one position momentary Operating Current Rating And Type: 80.0 milliamperes dc single winding Time Delay: 0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a		
Operating Current Rating And Type: 80.0 milliamperes dc single winding Time Delay: 0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a	Nonpile-up N	lain Contact Arrangement:
80.0 milliamperes dc single winding Time Delay: 0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a	4 pole, doub	e throw, one position momentary
Time Delay: 0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a		
0.015 seconds fixed operate and release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a	80.0 milliamp	eres dc single winding
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle 1.446 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a	Time Delay:	
1.446 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a		-
Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a	Center To Co	enter Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle
48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a		
Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a	Operating Vo	oltage Rating And Type At Specificationified Temp:
10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a	48.0 volts dc	25 degrees celsius single winding
Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a	Main Contac	t Load Current Rating At Maximum Rated Voltage:
115.0 ac and 28.0 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a	10.0 amperes	ac resistive load and 10.0 amperes dc resistive load
Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a	Main Contac	t Maximum Voltage Rating In Volts:
14 pin all functions <b>Shelf Life:</b> N/a	115.0 ac and	28.0 dc
Shelf Life: N/a	Terminal Typ	be And Quantity:
N/a	14 pin all fund	ctions
	Shelf Life:	
Unit Of Measure:	N/a	
	Unit Of Meas	sure:
	Demilitarizat	ion:

No

## NSN 5945-01-039-7369

Electromagnetic Relay - Page 2 of 2

**Fiig:** A03300

